Full Colour Multi Function Printer



RICOH IM C300 IM C300F IM C400F



Colour High-flyer

Keep up with your dynamic digital workplace

Future-Proof Technology at Your Fingertips

RICOH IM C300/ IM C300F/ IM C400F are categorised under the group of RICOH Intelligent Devices which provides smooth access to functionality upgrades and productivity enhancements when they are released. Not only does your device's software gets automatic updates to the latest features, you can also include additional functionality or smart solution that your businesses may require in the future. This means you no longer have to cope with the frustration of dealing with an out-of-date device. RICOH IM C300/ IM C300F/ IM C400F also assists organisations throughout the world to transform into digital workplaces by managing and converting information into intelligence with today's technology.

Learn more about RICOH's Dynamic Workplace Intelligence: https://www.ricoh-ap.com/dynamic-workplace-intelligence





Delivering Performance

With print speeds up to 30 or 43 pages per minute, RICOH IM C300/ IM C300F/ IM C400F powers your printouts at a faster speed, while ensuring crisp and sharp printouts at an impressive 1,200 x 1,200 dpi resolution. Lesser paper reloading is now achieved with the standard input paper tray capacity doubled to 550 sheets (IM C400F only) with a maximum paper input capacity (including bypass) of 2,300 sheets. Durability of the machine also doubles to a maximum of 600,000 paper outputs or 5 years, whichever comes earlier.

Intuitive Experience

Equipped with our industry-leading 10.1-inch Smart Operation Panel (SOP), RICOH IM C300/ IM C300F/ IM C400F not only delights you with an intuitive operating experience but also makes your work life easier. Applications and functions are seamlessly integrated with an easyto-understand interface. Furthermore, the SOP can be customised to match your usage behaviour, allowing RICOH IM C300/ IM C300F/ IM C400F to become your dependable print partner.



RICOH IM C300 / IM C300F / IM C400F

MODEL	RICOH IM C300	RICOH IM C300F	RICOH IM C400F	
GENERAL				
Functions	Copy, Print, Scan	Copy P	rint, Scan, Fax	
Operation panel		10.1" Smart Operation Panel		
Warm-up	19 seconds or less		17 seconds or less	
First output speed : B/W			6.2 seconds or less	
		7.2 seconds or less		
irst output speed : Full Colour		8.6 seconds or less		
Continuous output speed : B/W	30 ppm		43 ppm	
Continuous output speed : Full Colour	30 ppm 40 ppm			
PU	Intel® Apollo Lake E3930 1.3GHz			
/lemory	2GB standard/maximum			
IDD	320GB standard/maximum			
PDF capacity		50 sheets		
Veight (Mainframe)	47kg or less 50kg or less		50kg or less	
	Standard: 498 x 561 x 510 mm		Standard: 498 x 561 x 590 mm	
Dimensions (W x D x H)	Maximum: 498 x 561 x 954 mm		Maximum: 498 x 561 x 1,034 mm	
Power source	220 - 240V, 50/60Hz			
		220 - 2400, 30/00112		
OPIER		11 × 200 ×		
Iultiple copying	Up to 999 copies			
esolution	600 dpi			
oom	From 25% to 400% in 1% steps			
RINTER				
rinter language	Standard: PCL5c, PCL6, PostScript3 (Emulation), PDF Direct (Emulation) Option: XPS, Genuine Adobe® Postscript®3™, PDF Direct from Adobe®			
Print resolution	1.200 x 1.200 dpi			
The resolution	1,200 x 1,200 api			
letwork interface	Standard: Ethernet 10Base-T/100Base-TX/1000Base-T, 2xUSB Host I/F Type A, 1xUSB Device I/F Type B Option: Bi-directional IEEE1284/ECP, Wireless Lan (IEEE802.11a,b,g,n 2.4GHz or 5GHz), Additional NIC (2nd Port)			
Nobile printing capability	RICOH Smart Device Connector, Apple AirPrint [®] , Mopria [®] , NFC			
Vindows [®] environments	Windows® 7/ 8.1/10, Windows® Server 2008/2008 R2/2012/2012 R2/2016/2019			
Aac OS environments	MAC OS X Native v10.11 or later - PostScript 3 only			
INIX environments	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX			
AP [®] environments	SAP® R/3®, SAP® S/4®			
Other supported environments	Citrix XenDesktop 7.0/7.1, Citrix XenApp 7.5 and later			
SCANNER				
icanning speed	40ipm (Simplex) / 80ipm (Duplex)			
tesolution	600 dpi maximum			
Compression method	Т	TIFF (MH, MR, MMR, JBIG2), Grayscale, JPEG (Colour)		
ile formats	Single Page TIFF, Single Page JPEG, Single Page PDF, Single Page High Compression PDF, Single Page PDF-A, Multi Page TIFF, Multi Page PDF, Multi Page High Compression PDF, Multi Page PDF-A			
-lie formats				
ican modes	Email, F	older, Network TWAIN, USB, SD Card, SMB, FT	P, URL, NCP	
ACSIMILE				
lircuit	-	PS	STN, PBX	
ransmission speed		2 seconds		
Aodem speed		33.6 Kbps - 2,400bps with Automatic Shift Down		
lesolution	- 33.6 KDps - 2,400Dps with Automatic shift Down			
Compression method	- MH, MR, MMR, JBIG			
/lemory	-	4MB standard (Ap	pproximately 320 pages)	
ECURITY				
eatures	Windows Authentication, LDAP Authentication, Basic Authentication, User Code Authentication, 802.1.x Wired Authentication, Authentication Password Encryption, SSL communication, S/MIME, IPsec communication, HDD Encryption, SMTP over SSL/TLS, Transport Layer Security (TLS), Wireless Lan (WEP, WPA, 11i), Network Protocol, IP Filtering			
APER HANDLING				
ecommended paper size		A5 SEF - A4 SEF		
accommended paper size				
aper input capacity		Standard: 250 sheets (excluding bypass 100 sheets) Maximum: 2,000 sheets (including bypass 100 sheets) N		
aper output capacity		Standard: 100 sheets Maximum: 200 sheets		
aper weight	Standard Tray: 60 - 163g/m ² , Bypass: 60 - 220g/m ² , Duplex: 60 - 163g/m ² , Optional Tray: 60 - 163g/m ²			
aper types	Plain Paper, Recycled Paper, Colour Paper, Wate	Special Paper 1-3, Letterhead, Preprinted Paper rproof paper, Coated Paper, OHP, Label Paper,	er, Bond paper, Cardstock, Back Copied paper, Envelope	
COLOGY		in the second se		
	4 20014	l or loss	1,350W or less	
ower consumption : Maximum		1,200W or less		
	50.6W		60.7W	
	0.66W 0.65W			
Power consumption : Ready mode Power consumption : Sleep mode				
	0.34	kWh	0.48 kWh	
ower consumption : Sleep mode EC value		kWh	0.48 kWh	
ower consumption : Sleep mode EC value NPUT / OUTPUT TRAYS OPTION	0.34	kWh size: A5 SEF - A4 SEF / LG SEF, Paper weight: 60		
ower consumption : Sleep mode	0.34			

Fax Option Type M41 (For IM C300 only), Fax Connection Unit Type M41, PostScript3 Unit Type M41, XPS Direct Print Option Type M41, Caster Table Type M41, Device Server Option Type M37, VM Card Type M37, Camera Direct Print Card Type M37, IEEE 1284 Interface Board Type M19, OCR Unit Type M13, DataOverwriteSecurity Unit Type M19, Unicode Font Package for SAP[®] 1 License, Unicode Font Package for SAP[®] 10 License, Unicode Font Package for SAP[®] 100 License, Optional Counter Interface Unit Type M12, NFC Card Reader Type M13, IEEE 802.11a/g/n Interface Unit Type M19, File Format Converter Type M19

MINOSHA connect. experience.

URL: http://www.minosha.in

MINOSHA PRINT SOLUTIONS PRIVATE LIMITED

CORPORATE OFFICE: Plot No, 25, Okhla Phase- 3, New Delhi, 110020 Tel: 011- 42266250, Email: info@minosha.in, Service toll free number: 1800 103 0066 & 1800 116 600 REGISTERED OFFICE: Quest, 1073, Rajabhau Desai Marg, Behind Beau Monde Towers, Prabhadevi, Mumbai, Maharashtra- 400025

Tel: +91-22-69394444

Banglore, Chennai, Delhi, Hyderabad, Kolkata, Ahemdabad, Mumbai & Pune.

For more information, please contact: