A4 Mono Printer and MFP



RICOH P 311 M 320F



Stability and Performance

Ensure uninterrupted workflow with print-on-demand from anywhere functionality

Easy to change, long-lasting print cartridges

RICOH P 311 and M 320F offer an All-in-One print cartridge with a long-lasting 7,000 print yield. When you do need to replace the cartridge, there's no disruption to your workflow. Simply slot in the new one via the convenient full front-access design.





*Image shown is with optional tray

Easy document sharing digitally

The feature-rich RICOH M 320F multi-function printer is made for easy sharing of all your important information. The 35-sheet Automatic Reversing Document Feeder (ARDF) allows you to scan and send a full-colour presentation to colleagues for review instantly via multiple Scan-to capabilities, including Scan-to-Email, FTP, Folder, USB drive and more.

Work from anywhere

Access and share all your documents even when not in the office via the RICOH Smart Device Connector app on your mobile device. Mopria® or AirPrint® lets you send print jobs directly to your RICOH printer from your mobile phone. Once you're back in the office, simply pair your Android® device via the Near Field Communications (NFC) tag on the printer to authenticate and transfer information and print.





Security is in our DNA

Recognising your need to keep your data secure, we've added robust security layers. Protect confidential documents from unauthorised viewing with the Locked Print function. Network encryption also ensures data transmission remains secure.

RICOH P 311 / M 320F

MAIN SPECIFICATIONS

MODEL		RICOH P 311	RICOH M 320F
GENERAL			
Configuration		Desk	top
Technology		Laser (N	Mono)
Function(s)		Print	Print, Copy, Scan, Fax
Display panel		4-Line operation LCD	4.3" colour touch panel
Processor		350 MHz	400 MHz
Memory		128 MB	256 MB
Mobile capability		RICOH Smart Device Connector, Apple AirPrint®, Mopria®	
Printer language		PCL5e, PCL6, PostS	
Network protocol		TCP	TP
Interface Operating system	Standard	10Base-T/100Base-Tx (Ethernet), USB 2.0 Type A x 1— rear, USB 2.0 Type B— rear, NFC tag	10Base-T/100Base-Tx (Ethernet) USB 2.0 Type A x 2—1 x rear & 1x front, USB 2.0 Type B x 1— rear, NFC tag
	Optional	IEEE 802.11a/b/g/n/ac (Wire	ess LAN) and Wi-Fi Direct
	Windows®	Windows® 8.1, Windows® 10, Windows® Server 2012, Windows® Server 2012R2, Windows® Server 2016, Windows® Server 2019	
	Mac	Mac OS v10.10 - v11	
	Other	Linux	
PRINTER			
Ouplex printing		Aut	0
Print speed (A4)		32 ppm (Simplex), 13 ppm (Duplex)	
First print out time		7.1 seconds	
Warm up time		26 seconds or less	30 seconds or less
Print resolution		600 x 600 dpi (Default), Windows®: 600 x 600 dpi, 1,200 x 600 dpi, 1,200 x 1,200 dpi MAC: 600 x 600 dpi Linux: 600 x 600 dpi, 1,200 x 1,200 dpi	
Average print volume		700 - 5,800 pages	
Duty cycle		35,000 pages/month	
OPIER		35,000 pag	
Copy speed (A4)			Up to 32 ppm
Document feeder type		-	Automatic Reversing Document Feeder
Document feeder capacity		<u>-</u>	35 sheets
Resolution		•	300 x 600 dpi (ARDF), 600 x 600 dpi (Platen)
Multiple copy		-	Up to 99
Copy features		-	Zoom Range: 25%-400%, Image density: 5 levels, Image quality: Text, Photo, Mix
CANNER			Combined Copy, Memory Copy, ID Card Copy, Series Copy
		·	Money 12 impressions/minute Colours 4.5 impressions/minute
can speed (A4 ARDF)			Mono: 13 impressions/minute, Colour: 4.5 impressions/minute
Resolution		-	600 x 600 dpi (ARDF), 1,200 x 1,200 dpi (Platen), 19,200 x 19,200 dpi (PC TWAIN
Original size		-	A4
Bundled drivers		-	Network TWAIN, WIA
can to		·	Scan to email, Scan to folder, Scan to FTP, Scan to USB, TWAIN scanning
ACSIMILE			
Circuit		-	PSTN, PABX
Compatibility		•	T.30 (ITU-T SuperG3)
Resolution		-	Horizontal: 200 dpi-8dots/mm, Vertical 100 dpi-3.85dots/mm, 200 dpi-7.7dots/mm
ransmission speed		-	33.6 Kbps—2,400 bps with automatic shift down
Compression method		-	MH, MR, MMR
eception features		-	Automatic, Paperless fax, Manual, Main scan auto reduction
Other supported features		<u>.</u>	Quick dial—8 (20 digits for name, 40 digits for numbers), Speed dial—100 (20 digit name, 40 digits for numbers), Label registration for Quick/Speed, Redial—automa manual, Redial interval time—2 selections (5 minutes: default, 6 minutes), Only re
Other supported featu			last number, Direct fax number entry
			last number, Direct fax number entry
ECURITY authentication		Locked	
ECURITY authentication APER HANDLING			Print
ECURITY authentication APER HANDLING	size	Locked A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican	Print
ECURITY Authentication APER HANDLING ecommended paper s	size Standard		Print Oficio, Indian Legal, Envelopes, Australian Foolscap
ECURITY Authentication APER HANDLING ecommended paper s	1	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets
ECURITY uthentication APER HANDLING ecommended paper s aper input capacity	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets
ECURITY Suthentication APER HANDLING ecommended paper saper input capacity aper output capacity	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets ets, Maximum 550 sheets 50 sheets
ECURITY uthentication APER HANDLING ecommended paper s aper input capacity aper output capacity aper weight	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets ets, Maximum 550 sheets 50 sheets
ECURITY APER HANDLING ecommended paper s aper input capacity aper output capacity aper weight COLOGY	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets ets, Maximum 550 sheets 50 sheets
ecurity uthentication APER HANDLING ecommended paper s aper input capacity aper output capacity aper weight COLOGY imensions (W x D x H	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets tets, Maximum 550 sheets 50 sheets
ECURITY uthentication APER HANDLING ecommended paper s aper input capacity aper output capacity aper weight COLOGY imensions (W x D x H /eight	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg
ECURITY uthentication APER HANDLING ecommended paper s aper input capacity aper output capacity aper weight COLOGY imensions (W x D x H /eight ower consumption (A	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific	Print Oficio, Indian Legal, Envelopes, Australian Foolscap (s), Maximum: 300 sheets eets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg
ECURITY uthentication APER HANDLING ecommended paper s aper input capacity aper output capacity aper weight COLOGY timensions (W x D x H Veight ower consumption (N eady mode	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan)	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg c), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan)
ecurity uthentication APER HANDLING ecommended paper s aper input capacity aper output capacity aper weight COLOGY imensions (W x D x H //eight ower consumption (N eady mode nergy saver (Sleep)	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan)	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets tets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan)
ECURITY unthentication APER HANDLING lecommended paper s aper input capacity aper output capacity aper weight COLOGY Dimensions (W x D x H Weight ower consumption (N leady mode nergy saver (Sleep) lower source	Standard With optional paper tray	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan)	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets tets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan)
ECURITY uthentication APER HANDLING tecommended paper s aper input capacity aper output capacity aper output capacity of the colory of the consumption (N teady mode nergy saver (Sleep) ower source consumables	Standard With optional paper tray (i) Max)	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan) 220–240 V, 50/60 Hz, 4.3 Amps (Asia Pa	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets tets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan) iffic), 110 V, 60 Hz, 8.5 Amps (Taiwan)
ECURITY utthentication APER HANDLING tecommended paper s aper input capacity aper output capacity aper weight COLOGY Dimensions (W x D x H Veight ower consumption (N ready mode nergy saver (Sleep) ower source CONSUMABLES NO toner cartridges (H	Standard With optional paper tray) Max) () (Extra high yield)	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific) 63.8 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan) 220–240 V, 50/60 Hz, 4.3 Amps (Asia Pa	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets tets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan) iffic), 110 V, 60 Hz, 8.5 Amps (Taiwan)
ECURITY unthentication APER HANDLING lecommended paper s laper input capacity aper output capacity aper weight COLOGY bimensions (W x D x H Veight ower consumption (M leady mode nergy saver (Sleep) ower source CONSUMABLES unto toner cartridges (H loosumable yield mea	Standard With optional paper tray Max) (c) (Extra high yield)	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific) 63.8 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan) 220–240 V, 50/60 Hz, 4.3 Amps (Asia Pacific) Black: Approx.	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg c), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan) iffic), 110 V, 60 Hz, 8.5 Amps (Taiwan)
ECURITY unthentication APER HANDLING lecommended paper s aper input capacity aper output capacity aper weight COLOGY brimensions (W x D x H Veight ower consumption (N leady mode nergy saver (Sleep) ower source ONSUMABLES No toner cartridges (k lonsumable yield mea hipped with Starter T	Standard With optional paper tray Max) (c) (Extra high yield)	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific) 63.8 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan) 220–240 V, 50/60 Hz, 4.3 Amps (Asia Pa	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg c), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan) iffic), 110 V, 60 Hz, 8.5 Amps (Taiwan)
ECURITY unthentication APER HANDLING lecommended paper s laper input capacity aper output capacity aper weight COLOGY bimensions (W x D x H Veight ower consumption (M leady mode nergy saver (Sleep) ower source CONSUMABLES unto toner cartridges (H loosumable yield mea	Standard With optional paper tray Max) (c) (Extra high yield)	A4 SEF, A5 SEF/LEF. A6 SEF, B5 SEF, B6 SEF, LG, Mexican 250 sheets (Bypass: 50 shee Paper Bank PB1130: 250 she 125 sheets 52 to 16 370 mm x 392 mm x 262 mm Less than 13.0 kg 1,025 W (Asia Pacific) 63.8 W (Asia Pacific), 64.9 W (Taiwan) 0.72 W (Asia Pacific), 0.66 W (Taiwan) 220–240 V, 50/60 Hz, 4.3 Amps (Asia Pacific) Black: Approx.	Print Oficio, Indian Legal, Envelopes, Australian Foolscap ts), Maximum: 300 sheets ets, Maximum 550 sheets 50 sheets 2 g/m² 405 mm x 392 mm x 420 mm Less than 18.0 kg 2), 920 W (Taiwan) 65.7 W (Asia Pacific), 65.7 W (Taiwan) 0.87 W (Asia Pacific), 0.8 W (Taiwan) iffic), 110 V, 60 Hz, 8.5 Amps (Taiwan) 7,000 pages



URL: http://www.minosha.in

MINOSHA PRINT SOLUTIONS PRIVATE LIMITED

CORPORATE OFFICE: Plot No, 25, Okhla Phase- 3, New Delhi, 110020

Tel: 011- 42266250, Email: info@minosha.in, Service toll free number: 1800 103 0066 & 1800 116 600

REGISTERED OFFICE: Quest, 1073, Rajabhau Desai Marg, Behind Beau Monde Towers, Prabhadevi, Mumbai,

Maharashtra- 400025

Tel: +91-22-69394444
Banglore, Chennai, Delhi, Hyderabad, Kolkata, Ahemdabad, Mumbai & Pune.

For more information, please contact: